



Active T5-40

SCHOOL/ COLLEGE/ FACTORY TIMER



Features

- Programmable Automatic Schedule Timer
- 5 Program 40 Time Schedules In Each Program
- Selection of Particular Program at Desired Days.
- Changeable User Password
- Automatic Bell Ringing Based On Programming
- External Light On/Off Time Can Be Modified
- Provision For Time Management
- Manual On/Off for Bell & Light
- On Board Keypad With 32 Bit Lcd
- Micro-Controller Based System
- Communication for Software Rs232



1 Password
5 Separate Program
On Board Keypad with LCD Display




Auto Bell Ringing based on the programming
Connect with External Light PC
External Light Option

Automatic Schedule
Timer



Active T5-40

SCHOOL/ COLLEGE/ FACTORY TIMER



SPECIFICATION

POWER SUPPLY	
Maximum Power Consumption	24 Watts
DC /AC Main Supply	12-24 V / 2 Amps
RELAY-NORMALLY CLOSED	
Max Output Volt / current- Bellout	240 V/5 A
Max Output Volt / current- Appl	240 V/5 A
Max Output Volt / current - for Audio Player	5V/100 MA
ENVIRONMENTAL	
Environment	Light Industrial
Max Humidity	95% Non-Condensing
Operating Temperature	0°C To 45°C
Storage Temperature	-20°C~+ 60°C
PHYSICAL	
Colour	Grey Coloured Metal Box
Control Panel Dimensions(mm)	(H X W X L) = 135 X 35 X 90
Weight	420 g